



EPC-WHL-Din Rail

8th Gen Intel® Whiskey Lake Fanless Tiny System

- > 8th Gen Intel® Whiskey Lake-U 4 Core Ultra Low 15W Processor
- > Intel® UHD Graphics 620/610
- > Dual Gigabit Ethernet, HD Audio
- > Dual Channel Max up to 64GB DDR4 2400Mhz
- > Dual Expansion, M.2 Key-B/E
- > Dual HDMI w/CEC Controller (Factory Option)
- > TPM 2.0, RAID 0/1
- > Din Rail Type

+ Spec

System	
Processor	Intel® Core™ i7-8665UE Processor (8M Cache, up to 4.40 GHz) Intel® Core™ i5-8365UE Processor (6M Cache, up to 4.10 GHz) Intel® Core™ i3-8145UE Processor (4M Cache, up to 3.9GHz) Intel® Celeron® Processor 4305UE (2M Cache, 2.00 GHz)
System Memory	2x 260-Pin SO-DIMM Socket, Max. Up to 64GB DDR4 2400MHz
BIOS	AMI uEFI BIOS, 128Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	Monitoring System Temperature and Voltage with Auto Throttling Control
SBC	ECM-WHL
Expansion	
Expansion	1 x M.2 (Key-B, 2242/3042, PCIe, SATA, USB 3.0, USB 2.0, SIM Slot) 1 x M.2 (Key-E, 2230, PCIe, USB2.0, CNVi)
Storage	
Storage	1 x 2.5" Drive Bay (7mm) 1 x M.2 (2242) Key-B Support RAID 0/1
I/O	
USB	4 x USB 3.1
Antenna	2 x Antenna Mounting with Dust Protection Cover
Display	
Chipset	Intel® UHD Graphics 620 (i7-8665UE, i5-8365UE, i3-8145UE) Intel® UHD Graphics 610 (4305UE)
Resolution	2 x HDMI 1.4: Max. Resolution 4096x2160@24Hz
Multiple Display	Dual Display
System Control	
LED Indicator	1 x Power on/off LED on front side 1 x Storage Access LED on front side
Audio	
Chipset	Realtek ALC892
Ethernet	
Chipset	1 x Intel® I211AT 1 x Intel® I219LM
Ethernet Interface	10/100/1000 Base-Tx Gigabit Ethernet Compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Power Requirement	Power Input: Typical +12V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant
Power Type	AT/ATX (ATX is default setting)
Operating Temperature	With extended temperature peripherals: -10°C ~ 50°C (14°F ~ 122°F) with 0.5m/s air flow With extended temperature peripherals: -10°C ~ 40°C (14°F ~ 104°F) with 0.2m/s air flow With 2.5" hard drive: 0°C ~ 40°C (32°F ~ 113°F) with 0.5m/s air flow
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	2.65lbs(1.2KG)
Construction	Aluminum + Metal
Mounting Kit	
Dimension (L x W x H)	177mm x 123mm x 55mm (7" x 4.8" x 2.2")

Distributed by:



www.avalue.com.tw



Vibration Test	With SSD: 5Gms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis
Shock Test	With SSD : 10G, IEC 60068-2-27, Half Sine, 11ms, Z Axis
Drop	ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces
Certifications	
Certification Information	CE, FCC Class B
Software Support	
OS Information	Win 10, Linux
Power Requirement	
Adapter	Input: 100 ~ 240Vdc/ 50 ~ 60Hz Output: 12V/10A AC-DC 120W Adapter

Ordering

EPC-WHL-86-A1-2R
8th Gen Intel®Core™ Processor Core™ i7-8665UE Fanless Din Rail System

EPC-WHL-83-A1-2R
8th Gen Intel®Core™ Processor Core™ i5-8365UE Fanless Din Rail System

EPC-WHL-81-A1-2R
8th Gen Intel®Core™ Processor Core™ i3-8145UE Fanless Din Rail System

EPC-WHL-43-A1-2R
8th Gen Intel®Celeron 4305UE Fanless Din Rail System

Texim Europe

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 971 3293
F: +39 (0)39 971 3293
E: italy@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com