


KEEX-510T Series

Intel® Embedded Compact Extended Form Factor
with Intel® Haswell ULT Core™ Processors




- Intel® Haswell ULT Core™ Processors
- 1x DDR3L SO-DIMM Socket
- 2x DP, 1x 24-bit/2-ch LVDS
- 2x SATA, 1x mSATA
- 3x GbE, 4x USB3.0, 2xUSB2.0, 2x COM
- 2x mini-PCle Sockets (1x wafer for SIM card support)
- 8-bit Digital I/O supported (4-bit input/4-bit output)
- Watchdog Timer, Hardware Monitor, TPM, iAMT
- Wide operating temperature range from -20°C to 70°C

Distributed by:




• Block Diagram



Technical Information

CPU Support	Intel® Haswell ULT Core™ i3-4010U Processor (KEEX-510A) Intel® Haswell ULT Core™ i5-4300U Processor (KEEX-510T) Intel® Haswell ULT Core™ i7-4650U Processor (KEEX-510B)	Power Connector	One 1x4-pin, pitch 3.0mm Wafer for +12VDC input One 1x4-pin, pitch 2.5mm Wafer for HDD Power supply One 1x7-pin, pitch 1.25mm Wafer for Panel Power supply ATX/AT Mode Support ACPI 3.0 support
Memory	1x DDR3L SO-DIMM Socket	Expansion	2x mPCIe sockets 1x wafer for SIM card support
BIOS	AMI uEFI BIOS 1x 128Mb SPI Flash ROM onboard	Cooling	1x Wafer for +12VDC CPU Smart FAN support
Display	2x DP (on rear) 1x 24-bit/2-ch LVDS	Watchdog Timer	Programmable WDT to generate System reset event
Peripheral Support	2x SATA connectors 1x mSATA Sockets (Mixed with mPCIe socket) 2x wafers for COM port support (COM1 & COM2 support RS-232/422/485) 2x USB 2.0 4x USB 3.0 type A Connectors (on rear) 1x DIO (4-bit in and 4-bit out)	Hardware Monitor	Voltage and System temperature monitoring
MSIC Support	1x Header for Reset button, HDD LED and External Speaker 1x Header for Power button, Power LED and SM bus 1x Header for mPCIe activity LED	OS Support	Windows 7 / Windows 8 / Linux
LAN	2x RJ-45 Connectors for Dual GbE LAN (Intel I210-AT) 1x RJ-45 Connectors (Intel I218-LM)	Dimensions	Intel® ECX Form Factor (105 x 146 mm / 4.13" x 5.75")
Audio	1x header for Line-In, Line-Out and Mic-In 2x Wafers for Stereo Speaker output	Environmental Factors	Operation Temp: -20°C - 70°C Storage Temp: -40°C - 85°C Humidity: 0% - 95%
		RTC	Processor intergrated RTC
		Certification	CE, FCC Class A

KEEX-510T Series I/Os



Ordering Information

Article	Part No.	Description
KEEX-510A	B3EX510A-000000T	ECX CPU Board, Intel® Haswell Core™ i3-4010U Processor, 1x DDR3L SODIMM, 3x GbE, 1x LVDS, 2x DP, 4x USB3.0, 2x USB2.0, 2x COM, without TPM & iAMT support
KEEX-510T	B3EX510T-010000T	ECX CPU Board, Intel® Haswell Core™ i5-4300U Processor, 1x DDR3L SODIMM, 3x GbE, 1x LVDS, 2x DP, 4x USB3.0, 2x USB2.0, 2x COM, with TPM & iAMT support
KEEX-510B	B3EX510B-030000T	ECX CPU Board, Intel® Haswell Core™ i7-4650U Processor, 1x DDR3L SODIMM, 3x GbE, 1x LVDS, 2x DP, 4x USB3.0, 2x USB2.0, 2x COM, with TPM & iAMT support