

Technical Data Sheet

RRC-SMB-CAR Car/Truck Power Adapter



90 Watt automobile power adapter

Features:

- 90 Watt continuous output power (85W main-output + 5W USB-output)
- Ultra compact and lightweight car adapter
- Wide input voltage range
- USB charging port
- Worldwide approvals
- High safety standards (e. g. protection against short circuit, over current, over voltage, over temperature)
- For use in cars and trucks
- To power RRC-SMB-UBC and RRC-SMB-MBC charger

Applications:

- Suitable for portable or mobile devices as well
- Simultaneous power for a battery charger and USB compatible device

Specification

Input	
Voltage range	11 - 32VDC
Switch off voltage	10VDC
Standby current	Typically 40mA @ 11V input Typically 80mA @ 32V input
Input fuse	12A (in CLP)
Protection	Reverse polarity (input fuse in CLP) Under voltage protection Over temperature protection (latch-off reset)

Output	
Output 1 (main)	
Voltage range	24VDC nominal
Power	85W max.
Initial set tolerance	±3% max.
Load regulation ⁽¹⁾	- 80mV max. / A
Line regulation	±1% max.
Ripple & noise ⁽²⁾	< 200mV _{pk-pk}
Current limit	Constant current, 6A max.
Protection	Short circuit Over current protection (current limitation) Over voltage protection (latch-off reset) Over temperature protection (latch-off reset)
Output 2 (USB)	
Voltage	5VDC nominal
Current / Power	1A max. / 5W max.
Total tolerance ⁽³⁾	±5% max.
Protection	Short circuit Over current protection

Distributed by:



Technical Data Sheet

RRC-SMB-CAR Car/Truck Power Adapter



Environmental	
Cooling	Convection cooled
Temperature	Operating: -20°C to 40°C Non-operating: -40°C to 85°C
Pressure & altitude	Operating: 1200hPa to 795hPa max. 2000m above sea level Non-operating: 1200hPa to 115hPa max. 15000m above sea level
Humidity	5 to 95% r.H., non-condensing

General	
Input connector	Cigarette lighter adapter (CLP)
Output connector (output 1)	DC-Plug OD 5.5mm ID 2.1mm
Output connector (output 2)	USB receptacle, Type A
Efficiency ⁽³⁾	Typical 96% at 100% load
MTBF	>20000h @ 25°C ambient temperature and G _B per MIL-HDBK217F
Green procurement	WEEE RoHS
Indicator green LED	On: Flashing: Off: Power Failure Power on off
Ingress protection rating	IEC60529, IP40

Safety & EMC		
Regulatory approvals	Europe International USA/Canada Australia	CE CB Report IEC60950-1 cULus UL60950-1 RCM
Electromagnetic emissions	Europe USA	EN55022 class B, EN55024 FCC15 class B
Electromagnetic immunity	ESD immunity Electromagnetic field immunity Electrical fast transient/burst immunity test ISO-Impulses UNECE vehicle regulation	IEC61000-4-2, 4kV contact / 8kV air IEC61000-4-3, 80-2700MHz, 3V/m, AM 80%/1kHz IEC61000-4-4, +/-1kV, 5/50ns ISO7637-2, pulses 1, 2a, 2b, 3a, 3b, 4 E13 ECE Reg. 10

- other approvals on request

Mechanical details	
Housing dimensions (LxWxH)	115 x 53.7 x 21.5mm, without cables and connectors
Input cable length	100cm ±5%
Output cable length	100cm ±5%
Weight	250g, with cables and connectors

Notes

1. Load regulation is measured at the output connector and includes the voltage drop across the output cable.
2. Measured with a 0.1µF ceramic and a 10µF electrolytic capacitors across the output terminals. The oscilloscope bandwidth is set at 20MHz a co-axial cable will be used to measure it. The test condition is maximum load.
3. Power losses of input and output cables are not considered here.

Germany/Headquarters	USA	Hong Kong	China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T. Hong Kong	RRC power solutions Ltd. Room 520, Yuanlin Building, Aiguo Road No. 3066, Luohu District, Shenzhen 518021
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2376 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com	Tel.: +86 755 8374 1908 Fax: +86 755 8374 1861 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com