

D-3362

Features

- Vortex86DX3 1GHz SoC
- Onboard 2GB DDR3
- 2LANs + 16-bit GPIO + 4COMs
- 2.5" SATA SSD support (Optional)
- Operating in -20°C to +70°C
- +8 to +24VDC Input
- DIN rail support
- Auto Power On support
- EtherCAT support



Specifications

Part Number	D-3362-852C2-I	D-3362-851C1G2-I		
CPU	DM&P Vortex86DX3 - 1GHz			
RAM	DDR3 2GB RAM onboard			
BIOS	AMI BIOS			
Display	VGA, resolution support up to 1920 x 1080			
LAN	10/100Mbps LAN x1 10/100/1000Mbps LAN x1	10/100Mbps LAN x1 10/100/1000Mbps LAN x1		
USB	External x2 Internal x1 (for wireless dongle)	External x2 Internal x1 (for wireless dongle)		
SD Slot	Internal x1	Internal x1		
SATA	1	1		
RS232	2	1		
RS485	2	1		
GPIO	---	8-bit GPIO x2		
Dimension	152 x 104 x 54mm			
Power Requirement	+8 to +24VDC			
Weight	760g			
Operating Temperature	-20°C - +70°C			
Auto Power On	Support			
DIN Rail	Support			
O/S Support	Windows 7 Windows XP Professional POS Ready (WePOS)	Windows Embedded Standard 7 Windows Embedded 2009 QNX	Windows Embedded Compact 7 Linux VxWorks	Windows Embedded CE6.0 DOS Free BSD

