



Standard battery pack RRC2140 (3S1P) with 11.40V / 3880mAh / 44.2Wh

Features:

- Slim and flat standard battery pack with higher capacity and lower height than round cell packs with similar energy
- Allows to develop smaller and thinner portable devices with long runtime
- SMBus & SBDS Rev 1.1 compliant
- Fulfils JEITA standards, advanced temperature-dependent charging profile
 - Fastest charging
 - Maximized cycle life
- Impedance tracking and cell balancing
 - No manual recalibration necessary
 - Longest lifetime
- Comprehensive charging/discharging and passive safety systems
- Worldwide approvals
- Registered with recycling systems worldwide



Applications:

Suitable for use in slim devices for industrial and medical applications, etc.

Specification

General		Electrical Parameters	
Delivery status	30%	Nominal voltage	11.4V
battery capacity		Nominal capacity	3880mAh
Compliance information	CE / UN 38.3 / Gost / PSE / BSMI / TISI / RCM / EAC / CQC / UL2054 / KC / BIS / IEC 62133 / RoHS / FCC / REACH	Initial impedance	<200mΩ @ 1kHz at 20°C
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)	Max. charge current	2700mA
Storage temperature	-20°C to 60°C max. -20°C to 25°C recommended	Max. charge voltage	13.05V
		Cont. discharge	3780mA
		Max. discharge	5670mA
		Life expectancy @25°C	>300 cycles with min. 85% of initial capacity
		1.9A Charge/0.75A Discharge	
Battery Dimensions		Safety Parameters PCM	
Length	212.9mm +/-0.5	Overcharge detection voltage	4390mV/cell
Width	86.2 +/-0.4mm	Overcharge release voltage	4200mV/cell
Thickness	8.35mm +/-0.25	Overdischarge detection voltage	2750mV/cell
Weight	<255g	Overdischarge release voltage	3250mV/cell
Contacts	+,+,C,D,T,-,-	Overcharge detection current	3100mA
		Overdischarge detection current	6000mA

Recommended Accessories

Type	Product	Application
Standard Battery Charger	RRC-SMB-FPC	40W standard battery charger for optimized charging process with external power supply for worldwide use.
Battery Mating Connector	RRC-MC21-90-10 RRC-MC21-90-20	Mating Connector for standard smart batteries RRC2130, RRC2140. Available for 90° PCB mounting (top and edge).
Power Supply AC/DC	PS65	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-UBC/MBC/FPC.
AC Power Cable	210950 for USA/CAN/JPN 210951 for EU/KOR 211333 for UK/SGP 211334 for AUS/NZL	Country specific power cable for PS65.
CAR Adapter DC/DC	RRC-SMB-CAR	90W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-UBC/MBC/FPC, RRC-PMM240 or mobile devices.

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
D-66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
Suite 107-437
Yorba Linda, CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial Centre
2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 520, Yuanlin Building,
Aiguo Road No. 3066,
Luohu District,
Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)395 967 226
F: +39 (0)395 967 226
E: italy@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com