MTB



Terminal blocks A



Your drawings and notes

General data

Dimensional class: low Standard colour: green

Pitches: metric 3.5 mm, 7 mm (.138 in, .275 in) imperial 3.81 mm, 7.62 mm (.150 in, .300 in)

Screw dimension: M2

Operating temp. range: $-40 \,^{\circ}\text{C} \div +105 \,^{\circ}\text{C} \,(-40 \,^{\circ}\text{F} \div +221 \,^{\circ}\text{F})$

Certifications

UL (n. E167473)

300 V - 12 A factory wiring (10 A field wiring) - 28÷16 AWG - 2.7 lbf in for for 3.5, 3.81, 7, 7.62 mm pitch

VDE (n. 40021761)

130 V - 12 A - T 110 - 1 mm² for 3.5 mm and 3.81 mm mm pitch 450 V - 12 A - T 110 - 1 mm² for 7 mm and 7.62 mm pitch


IMQ (n. CA02.00900)

 $130\ \text{V}$ - T 110 - 17.5 Å - 1.5 mm² solid (12 Å - 1 mm² stranded) for 3.5 mm and 3.81 mm pitch 750 V - T 110 - 17.5 Å - 1.5 mm² solid (12 Å - 1 mm² stranded) for 7 mm and 7.62 mm pitch

CSA (n. LR102896)


300 V - 12 A - 30÷16 AWG 3.5 mm, 3.81 mm, 7 mm and 7.62 mm pitch

Application values for end-use equipment have to be in accordance to norms and applicable to it. The certifications of some product's versions could be pending, for more detailed and updated data please refer to our web site **www.sauro.net** or your representative Sales Manager






MTB_0M8 2 ÷ 12 poles, 3.5 mm / .138" pitch
MTB_0M9 1 ÷ 6 poles, 7 mm / .276" pitch
MTB_0MT 2 ÷ 12 poles, 3.81 mm / .150" pitch
MTB_0MT 1 ÷ 6 poles, 7.62 mm / .300" pitch




Straight, side stackable

MTB __008 2 ÷ 25 poles, 3.5 mm / .138" pitch MTB __009 2 ÷ 13 poles, 7 mm / .276" pitch MTB __00T 2 ÷ 25 poles, 3.81 mm / .150" pitch MTB __00T 2 ÷ 13 poles, 7.62 mm / .300" pitch




55°, modular

MTB__048 2 ÷ 25 poles, 3.5 mm / .138" pitch MTB__049 1 ÷ 13 poles, 7 mm / .276" pitch



55°, side stackable

MTB__068 2 ÷25 poles, 3.5 mm / .138" pitch MTB__069 2 ÷ 13 poles, 7 mm / .276" pitch




 Straight, modular, pegs
 1.108"

 MTB
 0M8-0000P 2÷12 poles, 3.5 mm .138" pitch

 MTB
 0M9-0000P 1÷6 poles, 7 mm .276" pitch

 MTB
 0MT-0000P 2÷12 poles, 3.81 mm .150" pitch

 MTB
 0M7-0000P 1÷6 poles, 7.62 mm .300" pitch



 Straight, side stackable, pegs

 MTB
 .008-0000P
 2-3 poles, 3.5 mm .138" pitch

 MTB
 .009-0000P
 2-3 poles, 7 mm .276" pitch

 MTB
 .00T-0000P
 2-3 poles, 3.81 mm .150" pitch

 MTB
 .00T-0000P
 2-3 poles, 7.62 mm .300" pitch





Contact details

The Netherlands



Elektrostraat 17 NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33 F: +31 (0)53 573 33 30 E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10 B-1731 Zellik

+32 (0)2 462 01 00 +32 (0)2 462 01 25

E: belgium@texim-europe.com

UK & Ireland







St. Mary's House, Church Lane Carlton Le Moorland Lincoln LN5 9HS

+44 (0)1522 789 555 +44 (0)845 299 22 26 E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92 D-25451 Quickborn

T: +49 (0)4106 627 07-0 F: +49 (0)4106 627 07-20 E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 F: +49 (0)89 436 086-19

E: germany@texim-europe.com

Austria



Warwitzstrasse 9 A-5020 Salzburg

+43 (0)662 216 026 +43 (0)662 216 026-66 austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12 DK-2970 Hørsholm

T: +45 88 20 26 30 +45 88 20 26 39

E: nordic@texim-europe.com

Italy



Via Matteotti 43 IT-20864 Agrate Brianza (MB)

+39 (0)39 971 3293 +39 (0)39 971 3293 italy@texim-europe.com

General information



info@texim-europe.com www.texim-europe.com





