


**IEC320-C13 (EU)**

Country of Origin: China  
 RoHS: yes  
 Application: For Class I. Appliances  
 Approvals: CEBC, KEMA, NF, OVE, VDE, IMQ, FI, S, D, N, ENEC, KC

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-022 16A/250V
Connector		IS-14 10A/250V
Rating		300/500V 70°C
Flex cord		H05VV-F
WEIGHT / PACKING	1pc	N.W.: 192 g / pc
	BOX	100 pcs / 1box
		G.W.: 18,9 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (UK)**

Country of Origin: China  
 RoHS: yes  
 Application: For Class I. Appliances  
 Approvals: ASTA, Singapore, ENEC

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-62 5A/250V
Connector		IS-14 10A/250V
Fuse		5A
Rating		300/500V 70°C
Flex cord		H05VV-F
WEIGHT / PACKING	1pc	N.W.: 202 g / pc
	BOX	75 pcs / 1box
		G.W.: 15,9 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (UL)**

Country of Origin: China  
 RoHS: yes  
 Application: For Class I. Appliances  
 Approvals: UL, CSA

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-305B 10A/125V
Connector		IS-14 10A/125V
Rating		300V 105°C
Flex cord		SVT
WEIGHT / PACKING	1pc	N.W.: 149 g / pc
	BOX	125 pcs / 1box
		G.W.: 20,2 kg / box
		0.55x0.36x0.20 [m]



**IEC320-C13 (Aus)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                SAA

Length/cord	1.8m / 3x0.75mm <sup>2</sup>	
Plug	SP-502B 10A/250V	
Connector	IS-14 10A/250V	
Rating	250/440V 75°C	
Flex cord	H05VV-F	
WEIGHT / PACKING	1pc	N.W.: 197 g / pc
	BOX	90 pcs / 1box
		G.W.: 17,6 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (Brazil)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                Inmetro, ENEC

Length/cord	1.8m / 3x0.75mm <sup>2</sup>	
Plug	SP27A 10A/250V	
Connector	IS-14 10A/250V	
Rating	300/500V 70°C	
Flex cord	H05VV-F	
WEIGHT / PACKING	1pc	N.W.: 158 g / pc
	BOX	120 pcs / 1box
		G.W.: 18,8 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (Swiss)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                +S, ENEC

Length/cord	1.8m / 3x0.75mm <sup>2</sup>	
Plug	SP-027C 10A/250V	
Connector	IS-14 10A/250V	
Rating	300/500V 70°C	
Flex cord	H05VV-F	
WEIGHT / PACKING	1pc	N.W.: 169 g / pc
	BOX	100 pcs / 1box
		G.W.: 17,4 kg / box
		0.55x0.36x0.20 [m]



**IEC320-C13 (C)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                CCC

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-506A 10A/250V
Connector		IS-14 10A/250V
Rating		300/500V 70°C
Flex cord		RVV
WEIGHT / PACKING	1pc	N.W.: 182 g / pc
	BOX	100 pcs / 1box
		G.W.: 19,3 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (AG)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                IRAM, ENEC

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-852 10A/250V
Connector		IS-14 10A/250V
Rating		300/500V 70°C
Flex cord		H05VV-F
WEIGHT / PACKING	1pc	N.W.: 179 g / pc
	BOX	100 pcs / 1box
		G.W.: 18,6 kg / box
		0.55x0.36x0.20 [m]


**IEC320-C13 (Italy)**

Country of Origin      China  
 RoHS                      yes  
 Application              For Class I. Appliances  
 Approvals                IMQ, D, CEBC, S FI, N, IMQ, NF, OVE, KEMA, +S, VDE

Length/cord		1.8m / 3x0.75mm <sup>2</sup>
Plug		SP-028 10A/250V
Connector		IS-14 10A/250V
Rating		300/500V 70°C
Flex cord		H05VV-F
WEIGHT / PACKING	1pc	N.W.: 158 g / pc
	BOX	100 pcs / 1box
		G.W.: 16,9 kg / box
		0.55x0.36x0.20 [m]

