

COMFORT CO2

Optimising comfort and ensuring the health of occupants

Functions: **CO2, temperature, humidity, alarm button, dry contact input**



MEASURE

- Periodically monitor :
 - temperature
 - humidity level
 - CO2 concentration
- Count the number of events on the alarm button or dry contact input



ALERT

- And/or trigger an alarm if:
 - high or low threshold(s) are exceeded
 - press the alert button
 - event on the dry contact input

Additional features:

- **User information:** indicator light on the unit
- **CO2 calibration:** automatic or manual via button or downlink
- **Data sending mode:** periodic and/or on events
- **Optimisation of autonomy:** historisation
- **Data accessibility:** redundancy
- **Alarm repetition** in case of persistent event
- **Error / fault management:** configuration error, low battery
- **Data time-stamping** (LoRaWAN)
- **Network quality test at start-up** (LoRaWAN)



Working environment

Ensuring air quality in the workplace for the comfort and health of users.



Schools, Colleges and High Schools

In response to legislation: monitoring and improving indoor air quality.

TECHNICAL SPECIFICATIONS



LoRaWAN ARF8373AB | Sigfox ARF8373CB

Mechanical specifications

Weight	146 g (battery included)
Dimensions	111 x 61 x 40 mm
Enclosure	IP20, Bayblend® FR3010 (PC/ABS) plastique, blanc
Mounting	Wall or laid flat

Operating conditions

Temperature	0°C / +50°C
Humidity	0 to 85% RH (non-condensing)

Device Power Supply

Battery Type	1 connectorized battery pack
--------------	------------------------------

Device configuration

Local device configuration	IoT Configurator
Remote device configuration	Downlink via the network or via the KARE platform or through the KARE platform
Configuration and firmware update over-the-air	KARE+ compatible
Security	PIN/PUK Code protection

Radio/Wireless

Supported regions	LoRaWAN EU863-870 / Sigfox RC1
Wireless Security	AES-128 data encryption (LoRaWAN only)
Class	LoRaWAN: Class A Sigfox: Class 0
Supported LoRaWAN features	OTAA, ABP, ADR, adaptive channel setup
RF transmit power	14 dBm
Sensitivity	-136 dBm LoRaWAN @SF12 / <-120 dBm Sigfox

Regulations and certifications

Standard	Directive 2014/53/UE (RED)
----------	----------------------------

Humidity SENSOR		Temperature SENSOR		CO2 concentration SENSOR	
Technology	CMOSens®	Technology	CMOSens®	Technology	NDIR
Resolution type	0.01 %HR	Resolution type	+/- 0.015°C	Measurement range	400 - 5000 ppm
Range	0 à 100 HR%	Range	-40°C / +125°C	Resolution	1 ppm
Typical tolerance of RH over T°	Figure 1	Accuracy	Figure 3	Precision	+/- 30 ppm + 3% de la mesure
Accuracy at 25°C	Figure 2				

Figure 1 Typical tolerance of relative humidity over Temperature




Figure 2 Tolerance of RH at 25°C





Figure 3 Temperature accuracy





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany - North

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany - South

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Søndre Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 9713293
E: italy@texim-europe.com