

# Contact sensor

## Monitor openings / closures



ALERT

- Alert in the event of :
  - intrusion
  - opening or closing
- Prevent beyond a certain number of openings / closings



MEASURE

- Count the time spent in the open or closed state.  
Ex: refrigerator door

### Additional features:

- **Data transmission:**
  - on detection of a change of state (opening or closing)
  - or by default every 12 hours (twice a day)
- **Error/fault management:** product error warning, configuration error, low battery
- **Data time stamping (LoRaWAN)**
- **Network quality test at start-up (LoRaWAN)**



Know the time spent in an open state for a refrigerator.



Detect the opening of a smoke extraction hatch.



Detect an intrusion (technical room, server room, hatches, windows...).

# TECHNICAL SPECIFICATIONS



## LoRaWAN ARF8170BA-B01 | Sigfox ARF8171BA-B01

### DRY CONTACTS

#### Mechanical specifications

Weight	90g (battery included)
Dimensions	105 x 50 x 27mm
Enclosure	IP67, EMERGE™ PC 8731HH grey resin (casing), EMERGE™ PC 8430-15 transparent resin (sole)
Mounting	DIN Rail, Tube, Wall, Collar

#### Operating conditions

Temperature	-25°C / +70°C
Humidity	0 to 85% RH (non-condensing)

#### Device Power Supply

Battery Type	1 replaceable battery
Expected Battery Life	With the default configuration: - Sigfox: 6 years - LoRaWAN: > 10 years

#### Device configuration

Local device configuration	IoT Configurator
Remote device configuration	Downlink via the network or via the KARE platform
Security	PIN/PUK Code protection

#### Radio/Wireless

Supported regions	LoRaWAN EU863-870 / Sigfox RC1
Wireless Security	AES-128 data encryption (LoRaWAN only)
Class	LoRaWAN: Class A   Sigfox: Class 0
Supported LoRaWAN features	OTAA, ABP, ADR, adaptive channel setup
RF transmit power	14 dBm (25 mW)
Sensitivity	-136 dBm LoRaWAN EU868 @SF12 -124 dBm Sigfox RC1

#### Regulations and certifications

Standard	Directive 2014/53/UE (RED)
----------	----------------------------

### PROXIMITY SENSOR

Detection	Magnetic detection
Cable Length	≈ 1.2 meter
Dimension	14 x 38 x 8.7 mm
Casing	IP67
Max distance between the 2 magnets for detection	15 mm
Operating temperature	-10°C to +85°C





## Headquarters & Warehouse

Elektrostraat 17  
NL-7483 PG Haaksbergen  
The Netherlands

T: +31 (0)53 573 33 33  
E: info@texim-europe.com  
Homepage: www.texim-europe.com



### The Netherlands

Elektrostraat 17  
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33  
E: nl@texim-europe.com



### Belgium

Zuiderlaan 14, box 10  
B-1731 Zellik

T: +32 (0)2 462 01 00  
E: belgium@texim-europe.com



### UK & Ireland

St Mary's House, Church Lane  
Carlton Le Moorland  
Lincoln LN5 9HS


T: +44 (0)1522 789 555  
E: uk@texim-europe.com



### Germany - North

Bahnhofstrasse 92  
D-25451 Quickborn

T: +49 (0)4106 627 07-0  
E: germany@texim-europe.com



### Germany - South

Martin-Kollar-Strasse 9  
D-81829 München

T: +49 (0)89 436 086-0  
E: muenchen@texim-europe.com



### Austria

Warwitzstrasse 9  
A-5020 Salzburg

T: +43 (0)662 216 026  
E: austria@texim-europe.com



### Nordic

Søndre Jagtvej 12  
DK-2970 Hørsholm

T: +45 88 20 26 30  
E: nordic@texim-europe.com



### Italy

Via Matteotti 43  
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 9713293  
E: italy@texim-europe.com