

Double level sensor

Monitor the evolution of a fluid level

Dry Contacts



Dual level sensor



ALERT

- Warn when the level rises or down
- Anticipating an overflow
- Prevent at the end of the tank

Additional features:

- Dual detection level
- Data transmission (by default):
 - on detection of a change of state (opening or closing):
 - or every 12 hours (twice a day)
- **Error/fault management:** product error warning, configuration error, low battery
- Data time stamping (LoRaWAN)
- Network quality test at start-up (LoRaWAN)



Monitor the level of a basin (retention, evacuation) or a tank.



Monitor the water level in a drainage nozzle to avoid overflows.

TECHNICAL SPECIFICATIONS



LoRaWAN ARF8170BA-B02 | Sigfox ARF8171BA-B02

DRY CONTACTS

Mechanical specifications

Weight	90g (battery included)
Dimensions	105 x 50 x 27mm
Enclosure	IP67, EMERGE™ PC 8731HH grey resin (casing), EMERGE™ PC 8430-15 transparent resin (sole)
Mounting	DIN Rail, Tube, Wall, Collar

Operating conditions

Temperature	-25°C / +70°C
Humidity	0 to 85% RH (non-condensing)

Device Power Supply

Battery Type	1 replaceable battery
Expected Battery Life	With standard configuration: - Sigfox: 5.6 years - LoRaWAN: >10 years

Device configuration

Local device configuration	IoT Configurator
Remote device configuration	Downlink via the network or via the KARE platform
Security	PIN/PUK Code protection

Radio/Wireless

Supported regions	LoRaWAN EU863-870 / Sigfox RC1
Wireless Security	AES-128 data encryption (LoRaWAN only)
Class	LoRaWAN: Class A Sigfox: Class 0
Supported LoRaWAN features	OTAA, ABP, ADR, adaptive channel setup
RF transmit power	14 dBm (25 mW)
Sensitivity	-136 dBm LoRaWAN EU868 @SF12 -124 dBm Sigfox RC1

Regulations and certifications

Standard	Directive 2014/53/UE (RED)
----------	----------------------------

DOUBLE LEVEL SENSOR

Detection	Contact detection
Cable Length	≈ 1 meter
Dimension	215 mm total length
Casing	Stainless steel 304
Liquid	Compatible with all types of non corrosive fluids
Typical operating pressure	1 Mpa (Max 5MPa)
Operating temperature	up to +120°C





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany - North

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany - South

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Søndre Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 9713293
E: italy@texim-europe.com