


 Traditional for wave soldering
**General data**

Dimensional class:	medium
Standard colour:	green
Pitches:	metric 5 mm, 7.5 mm, 10 mm (.197 in, .295 in, .394 in) imperial 5.08 mm, 7.62 mm, 10.16 mm (.200 in, .300 in, .400 in)
Screw dimension:	M3
Recommended/highest tightening torque:	0.5/0.6 Nm (4.42/5.31 lbf-in)
PCB thickness:	max. 2.4 mm (.094 in)
PCB hole diameter:	min. 1.4 mm (.055 in)
Stripping length:	5.5 ÷ 6.5 mm (.22 ÷ .26 in)
Operating temperature range:	-40 °C ÷ +105 °C (-40 °F ÷ +221 °F)
Contact resistance:	<15 mΩ
Insulation resistance:	>10 ⁹ Ω (500V DC)
Insulating material group:	I (CTI ≥ 600V)

Certifications

UL (n. E167473) *factory wiring - **field wiring

300 V - 17.5 A (*), 15A (**) - 30÷14 AWG - 7 lbf-in for 5 mm, 5.08 mm, 7.5 mm and 7.62 mm pitch
600 V - 17.5 A (*), 15A (**) - 30÷14 AWG - 7 lbf-in for 10 mm and 10.16 mm pitch

VDE (n. 40022749)

250 V - 17.5 A - T 110 - 1.5 mm² for 5 mm and 5.08 mm pitch
750 V - 17.5 A - T 110 - 1.5 mm² for 7.5 mm and 7.62 mm pitch
750 V - 17.5 A - T 110 - 1.5 mm² for 10 mm and 10.16 mm pitch



IMQ (n. EI056)

250 V - T 110 - 24 A - 2.5 mm² solid (17.5 A - 1.5 mm² stranded) for 5 mm and 5.08 mm pitch
750 V - T 110 - 24 A - 2.5 mm² solid (17.5 A - 1.5 mm² stranded) for 7.5 mm, 7.62 mm, 10 mm and 10.16 mm pitch


CSA (n. LR102896)

300 V - 17.5 A - 30÷13 AWG for 5 mm, 5.08 mm, 7.5 mm and 7.62 mm pitch
600 V - 17.5 A - 30÷13 AWG for 10 mm and 10.16 mm pitch


Application values for end-use equipment have to be in accordance to norms and applicable to it.
The certifications of some product's versions could be pending, for more detailed and updated data please refer to our web site www.sauro.net or your representative Sales Manager

Your drawings and notes**Straight, modular**


MSG_001 - 2÷25 poles, 5 mm / .197" pitch
MSG_003 - 2÷5 poles, 7.5 mm / .295" pitch
MSG_002 - 1÷13 poles, 10 mm / .394" pitch
MSG_005 - 2÷25 poles, 5.08 mm / .200" pitch
MSG_007 - 2÷3 poles, 7.62 mm / .300" pitch
MSG_006 - 1÷13 poles, 10.16 mm / .400" pitch

**90°, modular**


MSG_091 - 2÷25 poles, 5 mm / .197" pitch
MSG_093 - 2÷5 poles, 7.5 mm / .295" pitch
MSG_092 - 1÷13 poles, 10 mm / .394" pitch
MSG_095 - 2÷25 poles, 5.08 mm / .200" pitch
MSG_097 - 2÷3 poles, 7.62 mm / .300" pitch
MSG_096 - 1÷13 poles, 10.16 mm / .400" pitch

**270°, modular**


MSG_051 - 2÷25 poles, 5 mm / .197" pitch
MSG_053 - 2÷5 poles, 7.5 mm / .295" pitch
MSG_052 - 1÷13 poles, 10 mm / .394" pitch
MSG_055 - 2÷25 poles, 5.08 mm / .200" pitch
MSG_057 - 2÷3 poles, 7.62 mm / .300" pitch
MSG_056 - 1÷13 poles, 10.16 mm / .400" pitch

**Side stackable**

MSG_0A1 - 2÷25 poles, 5 mm / .197" pitch
MSG_0A2 - 2÷13 poles, 10 mm / .394" pitch
MSG_0A5 - 2÷25 poles, 5.08 mm / .200" pitch
MSG_0A6 - 2÷13 poles, 10.16 mm / .400" pitch

**Straight, modular, short circuited**

MSG_001-000C 2÷3 poles, 5 mm / .197" pitch
MSG_005-000C 2÷3 poles, 5.08 mm / .200" pitch

**90°, modular, short circuited**

MSG_091-000C 2÷3 poles, 5 mm / .197" pitch
MSG_095-000C 2÷3 poles, 5.08 mm / .200" pitch

Distributed by:



The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)39 971 3293
F: +39 (0)39 971 3293
E: italy@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com