


Data Sheet – CP1250 A4X (CoinPower®)¹

Distributed by:

www.texim-europe.com

Type Designation	CP1250 A4X
Type Number	63121
VKB Number	63121 101 501
Cell Code	INR1250
System	Graphite – layered metal oxide (LiNi _x Mn _y Co _z O ₂) MH13654
UL Recognition	1703758
WERCSmart ID	1703758
Nominal Voltage [V]	3.7 (average) (3,62V min)
Typical Capacity [mAh]	64 (at 0.1C from 4.3 V to 3.0 V at RT)
Nominal Capacity [mAh]	62 (at 0.2C from 4.3 V to 3.0 V at RT)
Minimum Capacity C [mAh]	60 (at 0.2C from 4.3 V to 3.0 V at RT)
Dimensions [mm] (without Tags)	
Diameter	12.1 +0.0/-0.3
Height	5.0 +0.1/-0.1
Weight. approx [g]	1.6 +0.2/-0.2
Charging Method	Constant Current + Constant Voltage
Charge Voltage [V]	4.30 ± 0.05
Initial Charge Current [mA]	Standard Charge ² : 30 Fast Charge ² : 60 Rapid Charge ³ : 120
Charging Cut-Off (a) or (b)	Standard Charge: 5 Fast/Rapid Charge: 3
a) by time [h]	1.2
b) by min current [mA]	3.0
Discharge Cut-Off Voltage [V]	180 @ 2s
Max. Pulse Discharge Current [mA]	120
Max. Continuous Discharge Current [mA]	Charge: 0 to 45 Discharge: -20 to 60
Operating Temperature [°C]	60
Cell Surface Temperature [°C]	1 Year at -20 to 20 °C > 90 3 Month at -20 to 45 °C > 90 1 Month at -20 to 60 °C > 85
Storage Temperature	
Capacity Recovery Rate⁴ [%]	< 0.5 @ 1kHz
Impedance Initial [Ω]	>500 (> 80% of C _{ini})
Cycle Life 0.5C/0.5C, 20 °C⁵ [Cycles]	UN 38.3 passed relevant tests acc. IEC 62133 passed
Safety	
Internal Approval	
Overcharge Test (4.8V, 3C, 12h)	passed

¹ Recommendations regarding Charging/Discharging and Safety (cf. Handling Precautions/Advanced Product Information) have to be accepted. Cell must not be used without external safety electronics (PCM – Protection Circuit Module)! The CoinPower cell may exclusively be used for the intended purpose. For medical applications please contact VARTA Microbattery. This product is protected by patents, please see: www.varta-aq.com/patents

² "CoinPower A4-Version Charging Document" must be observed.

³ "CoinPower A4-Version Charging Document" must be observed. Max. charging voltage: 4.00V ± 0.05V; min. charging temperature: 20°C.

⁴ After storage at initial cell voltage of 3.6 to 3.7 V / cell

⁵ typical values

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.


It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.





Headquarters & Warehouse

Elektrostraat 17
NL-7483 PG Haaksbergen
The Netherlands

T: +31 (0)53 573 33 33
E: info@texim-europe.com
Homepage: www.texim-europe.com



The Netherlands

Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10
B-1731 Zellik

T: +32 (0)2 462 01 00
E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
E: uk@texim-europe.com



Germany - North

Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
E: germany@texim-europe.com



Germany - South

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
E: austria@texim-europe.com



Nordic

Søndre Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
E: italy@texim-europe.com