EasyPack L



3.7 V | 1,200 mAh nominal | 4.5 Wh | VKB: 56456 701 099 (SoC 50%, EOL), 56456 701 012 (SoC 30%)




Circuit Diagram





MM: month two digits | Y: year one digit | R: week one digit



GENERAL (Battery with safety circuit and plastic housing)

Cell	LPP 503562 S
PCM	Yes
NTC	10 kΩ ± 1 %; B-value K 3,435 ± 1 %
ID	10 kΩ ± 1 %
Configuration	1S
Weight	Approx. 26 g

ELECTRICAL SPECIFICATION

Nominal voltage Rated capacity at (0.5 C / 0.2 C), 23 °C \pm 5 °C Watt-hour rating

Charging method
Max. charge voltage

Max. continuous charge current

Rec. charge cut off

Max. continuous discharge current

Rec. discharge cut off Internal impedance

Exp. cycle life at (1.0 C / 1.0 C), 23 $^{\circ}$ C \pm 5 $^{\circ}$ C

3.7 V

1,150 mAh min., 1,200 mAh nominal

4.5 Wh

Constant current + constant voltage

4.2 V


1,150 mA

By current 11.5 mA or timer 3.5 h 2,100 mA (limited by PTC)

3 V

Approx. 99 mΩ

≥ 500 cycles ≥ 70 %



CELL & BATTERY PROTECTION

Overcharge detection	$4.3 \text{ V} \pm 0.02 \text{ V}$ (0.8 sec. to 1.2 sec. delay, resume 4.1 V \pm 0.03 V)
Overdischarge detection	$2.4~V\pm0.035~V$ (76.8 sec. to 115.2 msec. delay, resume remove load and charging current)
Overcurrent detection	3.2 A to 5.2 A (9.6 msec. to 14.4 msec. delay)

ENVIRONMENTAL CONDITIONS

Charge	0 °C to +45 °C
Discharge	-10 °C to +60 °C
Storage	1 month at -20 °C to +60 °C \geq 80 %
	3 months at -20 °C to +45 °C ≥ 80 %
	1 year at -20 °C to +30 °C ≥ 80 %
Humidity	0 to 85 RH %

SAFETY CERTIFICATIONS

Please follow VARTA handling and safety precautions for Lilon & LiPolymer.

The cell used is a UL recognized component according to UL1642 and IEC 62133 ed. 2 certified.

The battery meets the requirements of battery directives and the battery parts are RoHS-compliant.

The battery is UL 2054 listed and certified according to IEC6213 3-2, IEC62133 ed.2 and UN38.3.





Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Texim Europe B.V. its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Texim"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Texim makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product.

It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time.

All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts.

Please contact us if you have any questions about the contents of the datasheet.

This may not be the latest version of the datasheet. Please check with us if a later version is available.



Texim Europe - contact details



Headquarters & Warehouse

Elektrostraat 17 NL-7483 PG Haaksbergen The Netherlands

T: +31 (0)53 573 33 33 E: info@texim-europe.com Homepage: www.texim-europe.com









The Netherlands

Elektrostraat 17 NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33 E: nl@texim-europe.com



Belgium

Zuiderlaan 14, box 10 B-1731 Zellik

T: +32 (0)2 462 01 00 E: belgium@texim-europe.com



UK & Ireland

St Mary's House, Church Lane Carlton Le Moorland Lincoln LN5 9HS

T: +44 (0)1522 789 555 E: uk@texim-europe.com



Germany - North

Bahnhofstrasse 92 D-25451 Quickborn

T: +49 (0)4106 627 07-0 E: germany@texim-europe.com



Germany - South

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: muenchen@texim-europe.com



Austria

Warwitzstrasse 9 A-5020 Salzburg

T: +43 (0)662 216 026 E: austria@texim-europe.com



Nordic

Søndre Jagtvej 12 DK-2970 Hørsholm

T: +45 88 20 26 30 E: nordic@texim-europe.com



Italy

Martin-Kollar-Strasse 9 D-81829 München

T: +49 (0)89 436 086-0 E: italy@texim-europe.com