

SPECIFICATION for APPROVAL

1. Product Purpose And General Description

Powered by a regulated 12 Volt DC power source, the CF-12LBD-2L1933W is designed to drive 9 strings of LED backlight Module.

It has been optimized for LED backlight as the following LIST:

LED SIZE	LCM Model	Brand	Remark

This product has the following features:


- Open LED protection.
- Constant LED current.
- 100% Full-Load Tested.
- Designed, Manufactured in Taiwan and Supported Worldwide.



SPECIFICATION for APPROVAL

2. Physical Dimension, Pin & Connector Assignment

Physical Dimension:



Note:

1. UNIT: mm
2. SIZE: 120 mm × 45 mm × 13 mm
3. PCB Thickness 1.6 mm
4. The Height of Top-side is 10 mm (Max)
5. The Height of Bottom-side is 1.4 mm

Pin & Connector Assignment:

CN1: CviLux CI0106M1HR0-LF or Equivalent

Pin No	Symbol	Description
1	VIN	DC +12V
2	VIN	DC +12V
3	ON/OFF	OFF=0V
		ON=+3V
4	DIM	MIN BRIGHTNESS: 3V
		MAX BRIGHTNESS: 0V
5	GND	GROUND
6		GROUND

CN2&CN3 : CviLux CP05-2-P1MRO or Equivalent

SPECIFICATION for APPROVAL

Pin No	Symbol	Description
1	LED +	Positive
2	LED -	Negative

3. Absolute Maximum Ratings (Note 1)

Rating	Symbol	Value	Units
Input Voltage	$V_{in,max}$	+13.5	V_{DC}
Operating Temperature	$T_{a,max}$	-25 -- +75	°C
Storage Temperature	$T_{s,max}$	-30 -- +80	°C
Operating Humidity (without dewdrop)	$H_{a,max}$	80 %	R.H
(without dewdrop)	$H_{s,max}$	95 %	R.H

(Note 1):

Reliable and predictable operation of the device is not guaranteed with applied stresses at or beyond those listed in “Absolute Maximum Ratings”. Operation at these limits may reduce device reliability and is therefore not recommended. Please refer to “Recommended Operating Conditions” for reliable operation of the device.

4. Recommended Operating Conditions (Note 2)

Rating	Symbol	Value	Units
Input Voltage	V_{in}	11.4 ~ 12.6	V_{DC}
Operating Temperature	T_a	20 ~ 40	°C
Operating Humidity	$H_{a,max}$	40 ~ 60 %	R.H

(Note 2):

Reliable operation above 50°C is possible if airflow is provided.

SPECIFICATION for APPROVAL
5. Electrical Characteristics and Specifications (Note 3)

Unless otherwise noted $V_{in}=12.0$ Volts DC, $T_a=25^{\circ}\text{C}$ and unit has been running for over 30 minutes.

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remarks (Test Condition)
Input Specification						
Input Voltage	V_{in}	10.8	12.0	13.2	V_{DC}	
Input Current	I_{in}	2.1	1.8	1.5	A_{DC}	
On/Off control	ON/OFF	-	3.0	-	V_{DC}	ON STATE
		-	0	-		OFF STATE
Dimming Control	DIM	-	3	-	V_{DC}	MIN BRIGHTNESS
		-	0	-		MAX BRIGHTNESS
Output Specification						
LED Forward Voltage (Refer to the specification of light bar)	V_f	-	17	-	V_{DC}	
LED Forward Current	I_f	315	330	345	mA_{DC}	

(Note 3)

Manufactured by CHEFREE Technology Corp., has been applied for all the measurements.