

Distributed by:



EMS31



LTE Cat.M
Multi Band
variants



Multi Design
Capability
(LGA)



Bearer
Independent
Protocol



Embedded
TCP/IP Stack



embedded
SIM



Highly
Compact
Size



Advanced
Temperature
Management



MTC LTE

Cinterion® EMS31 Wireless Module

LTE Cat. M1 for Highly Efficient 4G Connectivity

Cinterion® EMS31 Wireless Module

Delivering Highly Efficient LTE Cat. M1 Connectivity


Gemalto's Cinterion® EMS31 wireless module opens new possibilities for Internet of Things (IoT) solutions. Based on new LTE low-power wide area (LPWA) standards, it is the first module truly designed for industrial IoT use cases. It brings new technology for optimal radio coverage (up to 15 db enhancement), enhanced power management (up to 10 year battery life), and a new radio concept that allows one global hardware variant in the future, while delivering market proven Industrial Grade M2M features expected from Gemalto.

EMS31 integrates the latest CAT M1 technology features to transform LTE for M2M markets. Optimized connectivity is achieved through an Enhanced Coverage feature, which uses a special algorithm to allow for deep penetration into difficult coverage areas for example basements and warehouses. In addition, advanced power saving features help battery operated devices achieve up to 10 year lifetime. Power management is further increased through the module's clever wake-up/sleep mechanism. EMS31 features a new single antenna radio concept that reduces device complexity and saves costs.

The EMS31 also comes with a suite of Gemalto special features which have evolved through our 20 years of experience to help customers in all stages and aspects of implementation: from production, to network troubleshooting, to security and connectivity. EMS31 is ideal for a variety of applications including smart meters, industrial trackers, healthcare, and industrial sensors, where safe, reliable connectivity and longevity are more important than high data rate.

The Cinterion EMS31 wireless module is part of Gemalto's proven Industrial family, which offers reliability, M2M-optimized features and extreme efficiency for a range of cellular standards from 2G to MTC standards such as CAT1 and NB-IoT. Benefits include flexibility, backward and forward compatibility to support network evolution, and product longevity to maximize your technology investment. EMS31 is compatible with Gemalto's broad portfolio of trusted solutions and services that Connect, Secure and Monetize the entire industrial IoT ecosystem.

LTE Cat. M1: Highly Efficient 4G for IoT



Advanced Power Saving

In addition to standard power saving capabilities, a clever wake-up & sleep mechanism, EMS31 provides suspend and resume in less than a second. This reduced boot time saves significant power for many IoT devices.

Optional embedded MIM or eUICC

Offering an embedded MIM - a trusted Gemalto core competency - the module provides an integrated MIM with either a fixed operator subscription, or with remote subscription management and On Demand Connectivity (ODC) capabilities. Benefits of eMIMs and ODC include reduced Total Cost of Ownership (TCO) due to easy integration and simplified manufacturing and delivery logistics for high volume customers.

Flexible RF

A unique RF design allows flexible regional band configuration and operator specific software. While initial designs support 2 bands, the evolving flexible RF design will support global multiband variants up to 12 bands. This enables a single hardware design for global deployments along with simplified asset creation, easy logistics chain and improved management.

Gemalto M2M Support includes:

- > Personal design-in consulting for hardware and software
- > Extensive RF test capabilities
- > GCF/PTCRB conform pretests to validate approval readiness
- > Regular training workshops



Local engineers, a competent helpdesk, a dedicated team of R&D specialists and an advanced development center are the hallmarks of our leading support offer.

Cinterion® EMS31 Features

GENERAL FEATURES

- > LTE (FDD) 3GPP Release 13:
 - EMS31-US: LTE (2,4,12)
 - EMS31-V: LTE (4,13)
 - EMS31-X: LTE (2,4,12,13)
 - EMS31-J: LTE (1,8,18,19)
 - EMS31-W: LTE Multiband
- > Compatible with Cinterion® Industrial module footprint
- > Control via AT commands (3GPP TS 27.007 and 27.005)
- > Cinterion® AT commands
- > Supply voltage range 3.3 .. 4.5 V
- > Dimensions: 27.6 x 18.8 x 2.1 mm
- > Operating temperature Range
 - > -40°C to +85°C
- > IP services transparent and nontransparent TCP/UDP-client & server, HTTP/FTP/SMP client, TLS support for TCP/UDP/HTTP/FTP/SMTP clients
- > Weight: ca. 2.7 g
- > Full Gemalto M2M AT command set and services
- > Control via AT commands (Hayes, 3GPP TS 27.007 and 27.005)
- > SIM Application Toolkit, Rel. 99

SPECIFICATIONS

- > LTE Cat. M1, single antenna, half duplex
- > DL/UL max: 300 kbps / 375 kbps
- > SMS via NAS
- > SMS text and PDU mode
- > PBL Client
- > Verizon APN class handling

SPECIAL FEATURES

- > Embedded MIM prepared
- > Firmware updatable via application and Over the Air (OTA)
- > LWM2M support
- > eDRX
- > Power Saving Mode (PSM)

INTERFACES (LGA PADS)

- > Pads for primary LTE Antenna
- > High speed 8-line serial interface
- > 2 UICC and U/SIM card interfaces 1.8V / 3V (one for embedded SIM)
- > I²C, ADC interface
- > 2x Serial interface:
 - High-Speed Serial Interface (9 lines, 920 kbps)
 - Secondary High-Speed Serial Interface (4-wires, 920 kbp)

DRIVERS

- > Driver for Windows® 7 / Windows® 8 / Windows 10

APPROVALS

- > FCC, GCF, IC, UL, PTCRB
- > Mobile Operator Approvals: Verizon, AT&T certification
- > California RoHS
- > Further MNO approvals t.b.d.

Connect. Secure. Monetize.™

Gemalto's complementary offering of solutions, services and platforms helps enterprises unleash the power of the IoT, providing a solid foundation of Trust based on three key pillars:

- **Connect.** The backbone of any IoT solution, Cinterion M2M Modules, SIM/MIMs, Terminals and secure services provide future-proof, reliable connectivity for all vertical market IoT solutions.
- **Secure.** Gemalto's end-to-end security solutions protect devices, the network and the cloud while managing the entire application lifecycle.
- **Monetize.** Our agile Sentinel monetization solutions enable innovative business models and new revenue streams through embedded licensing, while our secure Application Enablement Platform speeds time to market.

For more information, please visit: www.gemalto/loT, www.facebook.com/gemalto, or Follow @gemaltoIoT on twitter



Distributed by:



www.texim-europe.com

➔ GEMALTO.COM/M2M

gemalto
security to be free

The Netherlands



Elektrostraat 17
NL-7483 PG Haaksbergen

T: +31 (0)53 573 33 33
F: +31 (0)53 573 33 30
E: nl@texim-europe.com

Belgium



Zuiderlaan 14 bus 10
B-1731 Zellik

T: +32 (0)2 462 01 00
F: +32 (0)2 462 01 25
E: belgium@texim-europe.com

UK & Ireland



St. Mary's House, Church Lane
Carlton Le Moorland
Lincoln LN5 9HS

T: +44 (0)1522 789 555
F: +44 (0)845 299 22 26
E: uk@texim-europe.com

Germany North



Bahnhofstrasse 92
D-25451 Quickborn

T: +49 (0)4106 627 07-0
F: +49 (0)4106 627 07-20
E: germany@texim-europe.com

Germany South



Martin-Kollar-Strasse 9
D-81829 München

T: +49 (0)89 436 086-0
F: +49 (0)89 436 086-19
E: germany@texim-europe.com

Austria



Warwitzstrasse 9
A-5020 Salzburg

T: +43 (0)662 216 026
F: +43 (0)662 216 026-66
E: austria@texim-europe.com

Nordic region



Sdr. Jagtvej 12
DK-2970 Hørsholm

T: +45 88 20 26 30
F: +45 88 20 26 39
E: nordic@texim-europe.com

Italy



Via Matteotti 43
IT-20864 Agrate Brianza (MB)

T: +39 (0)395 967 226
F: +39 (0)395 967 226
E: italy@texim-europe.com

General information



info@texim-europe.com
www.texim-europe.com